

AQUAPAD

PRODUCT DESCRIPTION

Ciranova Aquapad is a waterborne wood stain, based on micro pigments, to colour all kind of wood for interior use. Aquapad gives the wood a uniform appearance and does the nerve come into its own. Due to its special composition and ease of use Aquapad is ideal for coloring large surfaces with a buffing machine.

TECHNICAL DATA

COLOR	AVAILABLE IN 16 COLORS
SOLID CONTENT	DEPENDING OF THE COLOR
DENSITY	DEPENDING OF THE COLOR
VISCOSITY	+/- 11" DIN 4 AT 20°C

PREPARATION

Sand the wood with 120 to 150 grit. After sanding the sanding dust must be carefully removed.

USER INSTRUCTIONS

Stir well before use. It is recommended to test the chosen color first before you treat the entire surface. During use, the Aquapad must be stirred frequently.

To finish with a varnish or waterbased oil (FORTICO or OCULTO) a hardener can be added (10% hardener Aquapad). The Aquapad can also be blocked first with Hardwaxoil Magic or UN1CO (Clear, Natural White or Natural).

Take in account that there is a potlife of +/- 3 hours when the hardener is added. It's recommended only to sand after applying the first protection layer. When sanding after application of the Aquapad, there is a risk of color difference.

Aquapad needs to be applied evenly with a buffing machine. If the Aquapad is applied with a roller or brush you can equalize afterwards with a buffing machine (white or gray pad), cloth or dry brush. Don't leave used pads on the floor to avoid color differences.



DRYING TIMES

Dry after +/- 3 to 4 hours.

The drying time is strongly depending on the applied quantity, the temperature, air humidity and the ventilation of the room



APPLYING QUANTITY

10 to 15 m² / liter depending on the type of wood, preparation and application.

AFTER TREATMENT

After drying, the Aquapad must be protected by an oil, varnish or waxes out of the Ciranova range.

PRODUCT INFORMATION

All colors can be mixed

Shelf life: 1 year in closed and original packaging.

SPECIAL QUALITIES

Aquapad is not frost resistant. Do not use materials that can rust. The final color depends on the wood, sanding, and the quantity applied. Therefore it is recommended to always test the color on the wood!



5L

1L

Ciranova[®] products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare
tel +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48
www.ciranova.be ciranova@ciranova.be