

FORTICO SEALER



1L

5L



Ciranova® products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare
tel +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48
www.ciranova.be ciranova@ciranova.be

PRODUCT DESCRIPTION

FORTICO SEALER is a water-based one-component primer for application by roller with good filling properties. FORTICO SEALER can be used as a first coat for parquet floors to be finished with a lacquer from the FORTICO-range. FORTICO SEALER is recommended for use on floors with underfloor heating and tropical wood species or cork.

TECHNICAL DATA

VISCOSITY	+/- 30" DIN4
SOLIDS	+/- 35 % IN WEIGHT
DENSITY	+/- 1,05
LABELLING	SEE SDS
COVERAGE	APPROX. 100-130G/M ² PER COAT

APPLICATION

Especially suitable for tropical wood-species due to its elasticity or for parquet floors on underfloor heating. The SEALER avoids the side bonding effect and minimizes the grain raising effect. Also helps avoid the bleeding of tannin (with oak).

PREPARATION

Surface: Solid wood, Engineered Wood and Cork. First sand the wood, finish with 120 – 150 grit and remove the sanding dust. The finer the sanding grit, the less grain raising will occur. To reduce the grain raising effect, it is recommended to pre-wet the surface and to sand with a finer grit.

USER TIPS

Before use, stir and mix well FORTICO SEALER. Apply plentifully using a roller, approx. 80 -100g/m². Once dry, FORTICO SEALER can be finished with a lacquer from the FORTICO range.



DRYING TIMES

Dry after 2 to 3 hours.

The drying times are strongly dependent on applied quantity, temperature, air humidity and the ventilation in the room.



APPLYING QUANTITY

8 -12 m²/L

PRODUCT INFORMATION

- Durability: 12 months in original and closed packing.
- Transport and storage between 5°C and 40°C.
- FORTICO SEALER is not frost-durable.

SPECIAL QUALITIES

Use only stainless steel tools. Always clean immediately all tools after use. Don't pour this product into the sewerage systems. Some stains can bleed after use with FORTICO SEALER, therefore always test before use. When contact with air, water-based products can show a skinning. If necessary, filter in advance.