

OCULTO

PRODUCT DESCRIPTION

OCULTO is an invisible, water based impregnation oil for parquet and wooden furniture. The wood retains its original and untreated appearance. OCULTO is particularly suitable for interiors where a natural finish is needed such as parquet, veneer and other wooden objects. OCULTO is an Anti-slip finish and has UV inhibitors.

TECHNICAL DATA

VISCOSITY	+/- 16 SEC (DIN 4MM)
SOLID CONTENT	+/- 28% BY WEIGHT
DENSITY	+/- 1 KG/L
GLOSS	<5 GU /(60°)
DILUTION	CLEAR
ANTISLIP : DCOF 0,49 (>0,43 = HIGH SLIP RESISTANCE)	

PREPARATION

Substrate: solid wood, multilayer wood or veneer.

Prepare the floor according to the instructions.

Sand the wood with 120-150 grit sanding paper, and remove any sanding dust.

USER TIPS

OCULTO can be used as a sealer and topcoat and needs to be applied in 3 coats. Mix or stir the product well before use and don't dilute it. Application is done by a brush or roller. Apply the first layer wet in wet to avoid overlapping. When the first layer is dry, apply the second layer as the first layer. When the second layer is dry, sand with grain 150-180, remove sand dust and apply the third layer.

Optional, a hardener (10%) can be added in the 3 coats for improved durability. Add the hardener slowly by stirring till a homogenous mass.

DRYING TIMES

Dust free: 20 to 30 minutes

Sandable: 4 to 6 hours

Chargeable after 24 hours

The drying time is strongly depending on the applied quantity, the temperature, air humidity and the ventilation of the room. Through a higher temperature and good ventilation, drying time is limited.

APPLYING QUANTITY

10-12 m²/liter per coat

AFTER TREATMENT

Regularly maintenance with Hard Floor Fresh Ciranova[®]. For periodical maintenance, UNICARE X-MATT. Hard Floor Cleaner Ciranova[®] is used for cleaning very dirty floors and removing old polish layers.

PRODUCT INFORMATION

12 months in well-closed and unopened packing.

not frost-durable.

Pot life with hardener: +/- 3 hours.

SPECIAL QUALITIES

Use only stainless material. After use, rinse the material directly with water. This product cannot be poured into sewerage. If a stain on the wood is needed, only use Ciranova AQUAPAD + HARDENER.

Be aware of discoloration or detachment because of wood compounds like resins or tannin.



1L

5L

Ciranova[®] products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare
tel +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48
www.ciranova.be ciranova@ciranova.be